INKOMA / ALBERT

Great ideas need drive.





INKOMA-spiral bevel gear units type KL incorporate Klingelnberg Spiral Bevel Gears. This results in high efficiency and a very high torque transmission capability.

INKOMA-spiral bevel gear units are very quiet. Their compact and symentrical dimensions provide a space-saving drive layout.

Notable about this design is a newly patented feature of the INKOMA-spiral bevel gear unit type KL. This allows a simple means of backlash adjustment without the need for disassembly.


For normal applications the INKOMA-spiral bevel gear unit type KL is lubricated for life.


For applications involving particularly high speeds and duty a breather is provided and periodical lubricant replacement is advisable.


TECHNICAL INFORMATION

MODEL	RATIO
KL-0	1:1 / 1,5:1 / 2:1 / 3:1
KL-1	1:1 / 1,5:1 / 2:1 / 3:1 / 4:1 / 5:1 / 6:1
KL-2	1:1 / 1,5:1 / 2:1 / 3:1 / 4:1 / 5:1 / 6:1
KL-23	1:1 / 1,5:1 / 2:1 / 3:1 / 4:1 / 5:1 / 6:1
KL-25	1:1 / 1,5:1 / 2:1 / 3:1 / 4:1 / 5:1 / 6:1

INKOMA-SPIRAL BEVEL GEAR UNIT TYPE KL IS AVAILABLE IN THE FOLLOWING STANDARD VERSIONS








Special sizes and executions are possible, please enquire.

THE DESIGN OF THE INKOMA-SPIRAL BEVEL GEAR UNIT TYPE KL MAKES IT EASY TO USE IN COMBINATION WITH OTHER PRODUCTS



KL spiral bevel gear unit HSG precision screw jack GE cardan shaft

Request our complete catalogue or visit us on the Internet. You can obtain a free download of our brochure or the product drawing of the selected item using the CADENAS facility.

INKOMA / ALBERT

Great ideas need drive.



© Maschinenfabrik INKOMA 2014 Photography, layout, concept: www.fbwk.at

INKOMA Maschinenbau GmbH Lange Göhren 14 D- 39171 Osterweddingen T: +49 (0) 39205 453-0 F: +49 (0) 39205 453-433 info@inkoma.de